										·					
		4			3	\overline{V}	7 2						1		,
	DISCLOSED IN C	ON ON THIS DRAWING ONFIDENCE AND NO	T TO BE REPROD			CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06		C D .04 ±0.01	G 5 ±0.02	H ±0.01	·
	DISLOSED EXCE	PT FOR WHICH FURI	NISHED.			LB041434P-260		40-50 Navy 91/24 = 36.7 kcmil	?1/4			49 0.09		0.30	
								133/.0177 49/.029							
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													D	
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. Color coded barrel markings —BOLT SIZE														
	1	ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS													
			VISE SPECIFIE	ED IN THE SUFFIX (NO.									
	MATERIAL	: HIGH CC	NDUCTIVITY	WROUGHT COPPE	ER										
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С			
	—Wire inspection hole													4	
+>	DIE CODE DIE COLO			H									\leftarrow		
		_					\B	eveled wire entr		D					
В		շՄՆ	US R	oHS				•	,						В
		LISTED WIRE CONNECTOR													
		ZMVV/2/7/8.E51391													
	1														
							ш	JYA®	-			ORPC			
								nuyaco.com				. Zhongo ngzhou			
Α					TITLE WIRE CONNECTORS AND SOLDERING									Α	
				LUGS FOR CODE AND FLEX CABLE											
	00 04-May-2	5 Ruby Feng Sir	nia Qiu	Celestra Stand		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE WROUGHT COPPER LB041434P-260 NTS							ROJECTION		
ı	REV DATE		CHK	DESCF	RIPTION	ECN		CTRO TIN PLATE	6. NO. 1	86-cp265	1 UNIT	INCH	⊕ £		
		4			3	\triangle		2					1		