						I										
		4			3	$\overline{V}$	2				<u> </u>		1			,
	DISCLOSED	N CONFIDENCE AN	ID NOT TO BE RE	ROERTY OF CELESTRA, IS EPRODUCED, USED OR	5	CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLOSED E	(CEPT FOR WHICH	FURNISHED.			LB041434P-260		40-50 Navy 91/24 = 36.7 kcmil 133/.0177 49/.029	?1/4		1.39	0.49	0.09	0.75	0.30	
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														D	
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".														_	
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER  FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С				
	INSTALLATION GUIDE DIE CODE = 29 DIE COLOR = Gray  Wire inspection hole															
В	Beveled wire entry  Beveled wire entry														В	
																_
								JYA® nuyaco.com	7	<b>ELES</b> 6. Huai anyu D	ncun F	Rd. Zho	ongcu	n Tow		
А					WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE											
	-					MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PR LB041434P-260 NTS								OJECTION		
1	REV DA		CHK	DESC	CRIPTION	ECN		CTRO TIN PLATE	6. NO. <b>1</b>	86-cp265	1 UN	INC	сн   т	(H)		
		4			3	$\triangle$		2					1			