	_							I											
			4				3	\bigvee		2					1				
ı	DISCL	OSED IN CON	NFIDENCE AND	O NOT TO BE		OF CELESTRA, IS ED, USED OR		CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	'	
	DISLO	JSED EXCEPT	FOR WHICH	FURNISHED.				DB023801	#2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil	3/8	2.66	1.81	0.60	0.10	1.00	0.36		
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE														D				
_	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															_			
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С						
	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown Wire inspection hole												\leftarrow						
В	Beveled wire entry Beveled wire entry													В					
_	_																		
									CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495. TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
А																			
			Ruby Feng				dards Spec. Initialed.		WR	H-CONDUCTIVITY PRT. OUGHT COPPER	DB0	23801		CALE N	rs I	RID ANGLE PE	OJECTION		
1	REV	DATE	DWN	CHK		DESC	RIPTION	ECN		CTRO TIN PLATE	9. NO. 1	86-cp26	64 "	nit IN	CH	(E			
	_		4		1		3	\triangle		2					1				