			4 3 ψ 2				1										
I	DISCL	OSED IN CON		NOT TO BE	PROERTY OF CELES REPRODUCED, USED		CELESTRA CAT.NO	W CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLO	SLD LAGEFT	TOR WHICH	OKNISHED.			DB021243-250	#2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil	1/2	4.14	3.01	0.75	0.08	1.75	0.37	
D	N	OTE:		DIMENSION CIFIED.	NS ARE IN INCHES	UNLESS OTHERWISE											D
	 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 											js					
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
		ATERIAL:	HIG		TIVITY WROUGHT	COPPER		Die Color) (2					
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
\rightarrow	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown											\bigtriangledown					
В		Beveled wire entry														В	
		ZM/V/2/7/8 E513913															
A									JYA® nuyaco.com	7	6. Hua	ancun	Rd. Zh	iongcu	in Tow	_	
								A UGS FOR CODE AND FLEX CABLE									
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Celestr	a Standards Spec. Initialed.		WROUGHT COPPER DB021243-250 NTS									
I	REV	DATE	DWN	СНК	[DESCRIPTION	ECN		CTRO TIN PLATE	^{G. NO.} 1	86-cp26	71	INIT IN	СН 4	ΨL		
			4			3	4		2					ľ			