					I										
		4 3		$\bigvee$	2			1							
'			HE PROERTY OF CELESTRA SE REPRODUCED, USED OF		CELESTRA CAT.NO		RE SIZE	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G	H <u>⊧</u> 0.01	'
		T FOR WHICH FURNISHED			DB021458-251	CODE #2 AWG	FLEX 150/24 #2 Weld	1/4		1.43				0.42	
_															_
D	NOTE:	1 ALL DIMENSI	ONS ARE IN INCHES III	NI ESS OTHERWISE											D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														
			,LB,WP AND J SERIES		Color coded barrel markings										
			NDERWRITERS INC." <i>F</i> RES AND FLEX/24 STR	/—BOLT SIZE											
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS														
		OTHERWISE	SPECIFIED IN THE SUF												
		WITH "P".													
	MATERIAL:		CTIVITY WROUGHT CO												
С	FINISH:		I PLATE UNLESS OTHE ATE PER MIL - T -1636			, G⊸								С	С
		SUFFIX CAT.	IO.WITH "SP" FOR SILV	VER.		<b>P</b>	——А		->1						
							∕–Wire ins	nootion	, hala						
_							spection	THOLE			1			4	
$\rightarrow$	INSTALLATION DIE CODE =			H B B										+	
	DIE COLOR	= Brown				1							3		
									∱ D			ı			
			,			\Ве	veled wire entr	Ŋ	D						
В		C(Ui)	PoUS												В
			2002/95/EC												
		LISTED WIRE CONNECTORS ZMVV/2/7/8 E513813													
		ZMVV/2/78.E513913													
								C	ELES1	ΓΡΔ	COR	POR	ΔΤΙΩ	N	
						H	JYA®	7	6. Huan	cun F	Rd. Zha	ongcur	n Town		
				_		www.h	uyaco.com	Р	anyu Di	st. Gı	uangzh	nou 51′	1495.		
Α					TITLE WIRE CONNECTORS AND SOLDERIN									Α	
			+		LUGS FOR CODE AND						FLEX CABLE				
	00 23-Aug-25	Ruby Feng Sinia Qi	ı Celestra S	Standards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRII WROUGHT COPPER DB021458-251 NTS								JECTION	
	REV DATE	DWN CHK		SCRIPTION	ECN	EINIISH			86-cp2679	UN		$ +$ $\omega$	$\supset$	$\exists$	
		4	<u> </u>	3	$\triangle$		2		<u> </u>			1			
			1							1				-	