		4		3	$\overline{}$	2						11		
•			HE PROERTY OF CELESTR BE REPRODUCED, USED O		CELESTRA CAT.NO		RE SIZE	BOLT SIZE	A ±0.06 N			D G .015 ±0.02	H 2 ±0.01	
		T FOR WHICH FURNISHE			DB025601-261	CODE #2 AWG	FLEX 150/24 #2 Weld	5/16				.10 1.00		ĺ
					2202001.201		100/21 //2 110:0	0,.0					1 0	ĺ
D	NOTE:	4 ALL DIMENIC		NI FOO OTHERWISE										D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													
		2. ALL DA,DB,LA	,LB,WP AND J SERIES	OF CAT.NO.S ARE		Color coded barrel markings								
			NDERWRITERS INC." / RES AND FLEX/24 STR	/BOLT SIZE										
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS												 —	
			NO.WITH "L" HAS NOT SPECIFIED IN THE SUI											
		WITH "P".												
	MATERIAL:	HIGH CONDU	CTIVITY WROUGHT CO	OPPER										
С	FINISH:		I PLATE UNLESS OTHE ATE PER MIL - T -1636		⊸-G⇒									
			NO.WITH "SP" FOR SIL		A									
	—Wire inspection hole													
\rightarrow	INSTALLATIO	B B									\leftarrow			
DIE CODE = 33 DIE COLOR = Brown							2:							7
									<u> </u>					
						\Re	veled wire entr	7./	Ď					
В	Develed wife entry											В		
D		c(VL)us	RoHS											
		LISTED	2002/95/EC											
		WIRE CONNECTORS ZMVV/2/7/8.E513813												
								CE	ELEST	RAC	ORF	ORAT	ION	
							JYA®					ngcun To		
				_		www.h	uyaco.com	Pá	anyu Dis	st. Gua	ingzho	u 51149).	
Α					TITLE W	IRE CONN	NECTORS AND SOLDERING						Α	
				LUGS FOR CODE AND FLEX CABLE										
	00 23-Aug-25	Ruby Feng Sinia Qi	u Celestra S	Standards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID AN WROUGHT COPPER DB025601-261 NTS								
	REV DATE	DWN CHK		ESCRIPTION	ECN	EINIISH			36-cp2688	UNIT	INCH			
		4		3	\triangle		2		•			1		·
			ı		T					1				