			4	4 3 ψ 2					1								
I	DISCL	OSED IN CON		NOT TO BE	PROERTY OF CELES REPRODUCED, USEI		CELESTRA CAT.NO	W CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISEO	SLD LAGEFT	TOR WHICH	OKNISHED.			LB021243-242	#2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil	1/2	4.15	3	0.88	0.11	1.75	0.36	
D	N	OTE:		DIMENSION CIFIED.	IS ARE IN INCHES	SUNLESS OTHERWISE											
			LIST	ED BY "UNI	B,WP AND J SERI DERWRITERS INC S AND FLEX/24 S												
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	м	ATERIAL:	HIG	H CONDUCT	TIVITY WROUGHT	COPPER											
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
\rightarrow	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown											\downarrow					
В		Beveled wire entry														В	
		ZM/V/27/8.E513913															
A		HUYA www.huyaco.com								CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.							
								TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Celest	ra Standards Spec. Initialed	d.	WROUGHT COPPER LB021243-242 NTS									
I	REV	DATE	DWN	СНК		DESCRIPTION	ECN		CTRO TIN PLATE	^{G. NO.} 1	86-cp27	'01 U	^{NIT} IN	СН	ŧ L		
			4			3	4		2					1			