				1								ı					
	THE INFORMATION	4	AVINIO IS THE		TDA IC T	3	V	10/	2		1 .	<u> </u>	T -	1	<u> </u>		
	DISCLOSED IN CON	IFIDENCE AND	NOT TO BE F	PROERTY OF CELES REPRODUCED, USED			CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	±0.04	D ±0.015	+0.02	+0.01	
	DISLOSED EXCEPT	TOR WITHCHT	OKINISTIED.				LB025678-250	#2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil	5/16	3.05	1.64	0.66	0.10	0.88	0.37	
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE															D	
_	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  MATERIAL:  HIGH CONDUCTIVITY WROUGHT CORRER														—		
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER  FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С				
-	INSTALLATIO DIE CODE = : DIE COLOR =	Wire inspection hole  H  B  H  A  B  B  B  B  B  B  B  B  B  B  B  B										$\leftarrow$					
В		C UL LIST WIRE CONNE		RoHS 2002/95/EC				Ве	eveled wire entr	y	I	Ö		•			В
									JYA® nuyaco.com	7	ELES '6. Hua Panyu [	ncun	Rd. Zh	nongci	ın Tow	n.	
А						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE											
		, ,	Sinia Qiu			ds Spec. Initialed.		WR	H-CONDUCTIVITY PRT. OUGHT COPPER	LB025	678-250		cale N		RID ANGLE PI	ROJECTION	
	REV DATE	DWN 4	CHK		DESCRIP	TION 3	ECN		CTRO TIN PLATE	9. NO. <b>1</b>	86-cp27	05	nit <b>IN</b>	СН   - 1	<b>ψ</b> Ł		
				I			T					1					