								1											
			4 3 N ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS		∇	2					1								
	DISCLOSE	D IN CON	FIDENCE AND	NOT TO BE F				CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01		
	DISLOSED	EXCEPT	FOR WHICH	FURNISHED.				LB021034P-250		60 Navy #4 Weld 125/24 = 50.5 kcmil	#10	2.70	1.29	0.60	0.10	0.75	0.37		
D	NOT	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.															D		
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															_			
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER												С						
	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown Wire inspection hole H												\leftarrow						
В	Beveled wire entry														В				
	WIRE CONNECTORS ZMVV/27/8 E513913														_				
_										JYA® nuyaco.com	7	ELES '6. Hua Panyu D	ncun	Rd. Zh	nongci	ın Tow			
А									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	-						MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER LB021034P-250 SCALE THRID ANGLE F								_	ROJECTION			
1	REV [DATE	DWN	CHK		DESC	RIPTION	ECN		CTRO TIN PLATE	9. NO. 1	86-cp27	10 "	nit IN	CH -	+ E			
			4				3	4		2					1				