			4   3 $\checkmark$ 2					1									
I	DISCL	OSED IN COM		NOT TO BE	PROERTY OF CELES REPRODUCED, USED		CELESTRA CAT.NO	W CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLO	SLD LACEFT	TOR WHICH	ORNISHED.			LB021434P-250	#2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil	1/4	2.79	1.38	0.60	0.10	0.75	0.37	
D	N	OTE:		DIMENSION CIFIED.	NS ARE IN INCHES	UNLESS OTHERWISE											D
			LIST	ED BY "UNI	DERWRITERS INC	ES OF CAT.NO.S ARE ." AND "CSA" FOR USE IRANDED CABLES.	CSA" FOR USE										
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	м	IATERIAL:			TIVITY WROUGHT	COPPER		Die Color			) (	2					
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown											$\leftarrow$					
В		Beveled wire entry														В	
		WIRE CONNECTORS ZM/V/2/78.E513813															
A									JYA® nuyaco.com	7	6. Hua	incun	Rd. Zh	nongcu	RATIO	_	
							www.huyaco.com Panyu Dist. Guangzhou 511495.   TITLE WIRE CONNECTORS AND SOLDERING   LUGS FOR CODE AND FLEX CABLE										
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Celestr	a Standards Spec. Initialed.	WROUGHT COPPER LB021434P-250 NTS								OJECTION		
I	REV	DATE	DWN	СНК		DESCRIPTION	ECN		CTRO TIN PLATE	<sup>G. NO.</sup> 1	86-cp27	12 U	<sup>NIT</sup> IN	СН	⊕ E		
			4			3	4		2					1			