			4 3 \forall 2				1											
I	DISCL	OSED IN CON		NOT TO BE	PROERTY OF CELES REPRODUCED, USED		CELESTRA CAT.NO	W CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01		
	DISLO	SLD LAGEFT	TOR WHICH	ORNISHED.			LB023834P-250	#2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil	3/8	2.99	1.58	0.66	0.10	0.75	0.37		
D	N	OTE:		DIMENSION CIFIED.	NS ARE IN INCHES	UNLESS OTHERWISE											D	
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE											coded barrel markings						
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С		SPECIFED PLATE ONLESS OTHERWISE SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С				
\rightarrow	D	ISTALLATIO IE CODE = 1 IE COLOR =	33				<u>↓ {</u>	-Wire ins	pectio	n hole			\Rightarrow			\leftarrow		
В		H Beveled wire entry													В			
A								HUYA® www.huyaco.com HUYA® 76. Huancun Rd. Zhongcu Panyu Dist. Guangzhou 51							in Tow	n Town.		
							TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE											
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Celestr	a Standards Spec. Initialed.		WROUGHT COPPER LB023834P-250 NTS										
I	REV	DATE	DWN	СНК		DESCRIPTION	ECN		CTRO TIN PLATE	^{G. NO.} 1	86-cp27	16	INIT	СН	ŧ			
			4			3	4		2					1				