		4		3		$\downarrow$	7	2					1							
I	DISCL	OSED IN COM		D NOT TO BE	PROERTY OF CELES REPRODUCED, USE			ESTRA T.NO	CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01			
	DISLO	JLD LACEFT		I OKNISHED.			LB023	878P-250	#2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil	3/8	3.12	1.71	0.66	0.10	0.88	0.37			
D	N	OTE:		DIMENSION CIFIED.	IS ARE IN INCHE	S UNLESS OTHERWIS	E											D		
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.											. ← Color coded barrel markings								
											T SIZI	-								
0		ATERIAL:	HIG	H CONDUC					Die Color			) (						0		
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.													С						
$\rightarrow$	Wire inspection hole DIE CODE = 33 DIE COLOR = Brown										A A A A A A A A A A A A A A A A A A A		$\leftarrow$							
В		Beveled wire entry													В					
		ZM/V/2/7/8.E513813																		
A										JYA® nuyaco.com	7	'6. Hua	ancun	Rd. Zh		RATIC In Tow 11495.				
							TITLE WIRE CONNECTORS AND SOLDERING A   LUGS FOR CODE AND FLEX CABLE A													
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Celes	ra Standards Spec. Initi	aled.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER LB023878P-250 NTS											
1	REV	DATE	DWN	СНК				ECN		CTRO TIN PLATE	<sup>G. NO.</sup> 1	86-cp27	17 U	NIT IN	СН	Q L				
			4			3	4	7		2					1					