			4 3 2			1											
I	DISCL	OSED IN CON	FIDENCE AND	NOT TO BE	PROERTY OF CELES REPRODUCED, USED		CELESTRA CAT.NO	W CODE	IRE SIZE	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	-URNISHED.			LB023843P-250		60 Navy #4 Weld 125/24 = 50.5 kcmil	3/8	3.99	2.58	0.66	0.10	1.75	0.37	
D	N	OTE:		DIMENSION CIFIED.	IS ARE IN INCHES	UNLESS OTHERWISE											D
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE											ed barrel markings					
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
		ATERIAL:	HIG	H CONDUC				C									
С	C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.														С		
$\rightarrow$	D	ISTALLATIC IE CODE = 1 IE COLOR =	33					-Wire ins	pection	n hole —≃∣			$\rightarrow$			$\leftarrow$	
В		H Beveled wire entry													В		
A		HUYA 76. HU							6. Hua	STRA CORPORATION uancun Rd. Zhongcun Town. J Dist. Guangzhou 511495.							
							TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Celestr	a Standards Spec. Initialed.		WROUGHT COPPER LB023843P-250 NTS									
I	REV	DATE	DWN	СНК	[	DESCRIPTION	ECN		CTRO TIN PLATE	<sup>G. NO.</sup> 1	86-cp27	19 <sup>U</sup>	<sup>NIT</sup> IN	СН	<b>@</b> E		
			4			3	4		2					1			