								L											
			4		IS THE PROERTY OF CELESTRA, IS			V	2					_	1			,	
	DISCLO	OSED IN CON	NFIDENCE AND	O NOT TO BE				CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	±0.04	D ±0.015	G ±0.02	H ±0.01		
	DISLOS	SED EXCEPT	FOR WHICH	FURNISHED.				LB021243P-250		60 Navy #4 Weld 125/24 = 50.5 kcmil	1/2	4.42	3.01	0.75	0.08	1.75	0.37		
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.															D			
_	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															_			
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С						
	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown Wire inspection hole												\leftarrow						
В	Beveled wire entry Beveled wire entry													В					
			ZMVV/2/7/8															_	
										JYA® nuyaco.com	7	ELES '6. Hua Panyu [incun	Rd. Zh	nongci	ın Tow			
А									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00	24-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					WROUGHT COPPER LB021243P-250 NTS								RID ANGLE PI	ROJECTION			
ı	REV	DATE	DWN	CHK		DESC	RIPTION	ECN		CTRO TIN PLATE	9. NO. 1	86-cp27	20 0	nit IN	СН	(] ,	
			4				3	\triangle		2					1				