	_								I																
			4				3		\bigvee		2					1									
ı	DISCL	OSED IN CON	I ON THIS DRA NFIDENCE ANI I FOR WHICH	O NOT TO BE		OF CELESTRA, IS ED, USED OR			CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01] '						
	DISLO	SED EXCEPT	FOR WHICH	FURINISHED.					LB021243-260	#2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil	1/2	4.33	2.83	0.81	0.12	1.75	0.36							
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														D										
_	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS COlor coded barrel markings BOLT SIZE														_										
	 	IATERIAL:	WIT	H "P".		N THE SUFFIX	X OF THE CAT.N	IO.																	
С														С											
	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown Wire inspection hole																								
В	Beveled wire entry Beveled wire entry													В											
_	<u> </u>	ı	ı	1						ı									_						
Α									HUYA® Www.huyaco.com CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.																
					_				WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE																
			Ruby Feng				ndards Spec. Initia	aled.		WR	H-CONDUCTIVITY PRT. OUGHT COPPER	LB021	243-260		CALE N	rs I	_	LE PROJECTION							
1	REV	DATE	DWN	CHK		DESC	CRIPTION		ECN		CTRO TIN PLATE	6. NO. 1	86-cp27	21 U	nit IN	CH	(H) (E)	\supset] ,						
	_		4				3		\triangle	:	2					1									