	_							L										
			4		BROSEREN	05 051 5073 16	3	V						1	1		,	
	DISC	LOSED IN CON	NFIDENCE AND	NOT TO BE F		F CELESTRA, IS D, USED OR		CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISL	OSED EXCEPT	FOR WHICH	FURNISHED.				LB023878-260	#2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil	?3/8	3.21	1.71	0.60	0.11	0.88	0.36	
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														D			
_	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															_		
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С					
	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown Wire inspection hole												\leftarrow					
В	Beveled wire entry Beveled wire entry													В				
_	_		ZMVV/2/7/8															_
										JYA® nuyaco.com	7	ELES '6. Hua 'anyu [ncun	Rd. Zh	ongci	ın Tow		
А					_			WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00	23-Aug-25	Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDUCTIVITY PRT. NO. LB023878-260 SCALE NTS THRID ANGLE								_	ROJECTION	
ı	REV	/ DATE	DWN	CHK		DESC	RIPTION	ECN		CTRO TIN PLATE	9. NO. 1	86-cp272	28 U	nit IN	СН -	⊕ €		
	_		4				3	\triangle		2					1			