	-																	
		4 INFORMATION ON THIS DRAWING IS THE PROERTY OF CELE			3	∇	2						1					
	DISCL	OSED IN CON	NFIDENCE AND	NOT TO BE	PROERTY OF (REPRODUCED,			CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLO	OSED EXCEPT	FOR WHICH	FURNISHED.				LB021434P-260		60 Navy #4 Weld 125/24 = 50.5 kcmil	?1/4	2.89	1.39	0.60	0.11	0.75	0.36	
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														D			
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															_		
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER													С				
	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown Wire inspection hole H													\leftarrow				
В	LISTED WIRE CONNECTORS													В				
_		_	ZMVV/2/7:8	.E513913														_
										JYA® nuyaco.com	7	ELES '6. Hua 'anyu D	ncun	Rd. Zh	ongcl	ın Tow	_	
Α							WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE											
	00	0 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					ards Spec. Initialed.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE P WROUGHT COPPER LB021434P-260 NTS								ROJECTION		
ı	REV	DATE	DWN	CHK		DESCR	IPTION	ECN	FINISH ELEC	CTRO TIN PLATE	6. NO. 1	86-cp273	32 UI	nit IN:	СН	⊕ €		,
			4				3	$ \uparrow $		2					1			