	-			1			4					ı					
	THE INCORMAT	4	MANINO IO TUE	DDOEDTY OF OFFICE	TDA IC	3	V	10.0	2	I · -		<u> </u>	-	1	_		,
	DISCLOSED IN (	CONFIDENCE AN	D NOT TO BE	PROERTY OF CELES REPRODUCED, USED			CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	±0.04	D ±0.015	G ±0.02	+0.01	
	DISLOSED EXC	EPT FOR WHICH	FURNISHED.				LB023801P-251	#2 AWG	150/24 #2 Weld	3/8	3.44	1.83	0.70	0.11	1.00	0.42	İ
D																	D
D	NOTE:		DIMENSION CIFIED.	IS ARE IN INCHES	S UNLESS O												
				B,WP AND J SERI	Color coded barrel markings												
				S AND FLEX/24 S	/—BOLT SIZE												
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																
			HERWISE SF H "P".	PECIFIED IN THE S	SUFFIX OF T	HE CAT.NO.	o.										
	MATERIA	.: HIG	H CONDUCT	TIVITY WROUGHT	COPPER												
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE  SPECIFED PLATE PER MIL - T -16366.  SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С				
									/-Wire ins	pectio	n hole						
$\rightarrow$		TION GUIDE						1		В	—⇒		,				4
	DIE CODE							<b>H</b>			_   _	<u>!</u>		Ψ,	$\setminus$		1
								1				Ī			_)		
								\Вє	eveled wire entr	V		)					
В				V						,							В
		c	<b>L)U</b> S	RoHS 2002/95/EC													
		LIS	TED														
		WIRE CON ZMVV/2/7/															
	_																<b> </b> —
								<u> </u>									
								HI	JYA®				COF			_	
									uyaco.com				Rd. Zh Suangz			11.	
Α																	Α
							WIRE CONNECTORS AND SOLDERIN LUGS FOR CODE AND FLEX CABLE										
					_				H-CONDUCTIVITY PRT.		. /\INL		CALE		D ANGLE PR	O IECTION	
	<u> </u>	Ruby Feng	_			Spec. Initialed.	501	FINISH	DUGHT COPPER	LB0238	01P-251	4	TM	<u>s</u> 4			
1	REV DATE		CHK		DESCRIPT		ECN	ELEC	TRO TIN PLATE	1	86-cp27	41   "	IN	CH /	\(\psi\)		1
	-	4			3	3	4		2					1			
							•										