		4				ı		_					
	THE INFORMATION	4 I ON THIS DRAWING IS T	 THE PROERTY OF CELESTR	3	CELESTRA	2 RA WIRE SIZE BOLT		BOLT	<u> </u> A	вС	1 	G H	¬ '
	DISCLOSED IN CON		BE REPRODUCED, USED O		CAT.NO	CODE	FLEX			IIN ±0.04		-	
					LB023801P-261	#2 AWG	150/24 #2 Weld	3/8	3.46 1.	83 0.68	0.10	1.00 0.41	_
D													D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.												
		2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE											
			JNDERWRITERS INC." . IRES AND FLEX/24 STR		/_BOLT SIZE								
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS												
			SPECIFIED IN THE SU		NT.NO.								
	MATERIAL:			ODDED		Die							
_											C		
С	T IIVIOTI.	SPECIFED P	LATE PER MIL - T -1636										
		SUFFIX CAT.	NO.WITH "SP" FOR SIL	VER.									
							/-Wire ins	spection	hole				
	INSTALLATIO	ON GUIDE	1 8///										
	DIE CODE = 33 DIE COLOR = Brown										\		
	DIE 002010	- 510W1								(-			
						\Be	eveled wire entr	v	Ď				
B Beveled wire en							voica vino ona	·· J					В
J													
	"	ISTED	S/EC										
	WIF ZM	RE CONNECTORS VV/277/8.E513813											
		<u> </u>					<u> </u>			DA 00		ATION	-
						H	JYA®	CE			RPOR Thongcur	ATION	
							uyaco.com				zhou 51'		
Α				TITLE WIRE CONNECTORS AND SOLDERING						ING	Α		
				LUGS FOR CODE AND FLEX CABLE									
	00 09-Dec-25	Ruby Feng Sinia Q	Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE WROUGHT COPPER LB023801P-261 NTS						
	REV DATE	DWN CHK		ESCRIPTION	ECN	FINISH		0.110	6-cp2745	LINIT			
		4		3	<u> </u>		2		-		1		-
			'		I					•			