	•		4				3	<b>\psi</b>		2					1			
ı	DISCL	OSED IN CON	VEIDENCE AND	NOT TO BE		OF CELESTRA, IS ED, USED OR		CELESTRA CAT.NO	WIRE SIZE  CODE FLEX		BOLT SIZE	A ±0.06	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	'
D	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				DB015678-250	#1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223			1.64	0.70	0.11	0.88	0.42	D
	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE																
	_	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  -														_		
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  BOLT SIZE																	
С		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER  FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
<b>→</b>	D	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green  Wire inspection hole													$\leftarrow$			
В		il COLON :	C UI		Rol	HS.			↓ H ↓ Be	eveled wire entr	B		,					В
																		_
							HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.											
Α								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	ards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. DB015678-250 SCALE NTS THRID ANGLE PI					ROJECTION	ECTION			
ı	REV	DATE	DWN	CHK		DESCR	IPTION	ECN		CTRO TIN PLATE	G. NO. <b>1</b>	86-cp275	2 UN	IN IN		<b>⊕</b> Ł	$\supset$	
			4				3	4		2					1			