			4				3	\rightarrow		2					1			
ı	DISCL	OSED IN CON	NFIDENCE AND	NOT TO BE		F CELESTRA, IS ED, USED OR		CELESTRA CAT.NO			BOLT SIZE	A ±0.06	B MIN	C +0.04	D ±0.015	G +0.02	H ±0.01	'
D	DISLO	SED EXCEPT	FOR WHICH I	FURNISHED.			_	DB011243-250	#1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223			3.01	0.75	0.09	1.75	0.42	D
	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE												_				
_		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.													_			
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". Color coded barrel markings —BOLT SIZE																	
0		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE ODECUTED BLATE DED MILL TO 1999																
С		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С				
	D	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green —Wire inspection hole																
В		CULUS BOURS Beveled wire entry Beveled wire entry													В			
																		_
							HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.											
А								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	ırds Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER DB011243-250 NTS							ф -	PROJECTION	
ı	REV	DATE	DWN	CHK	_	DESCR		ECN		CTRO TIN PLATE	9. NO. 1	86-cp275	4 UN	IN IN		⊕ Ł	\Box	
			4		1		3	\triangle		2					1			