	•		4				3	<b>\psi</b>		2					1			
ı	DISCL	OSED IN CON	VEIDENCE AND	NOT TO BE		OF CELESTRA, IS ED, USED OR		CELESTRA CAT.NO	WIRE SIZE CODE FLEX		BOLT SIZE	A ±0.06	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	'
D	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				DB015678-260	#1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	<b></b>		1.58	0.68	0.10	0.875	0.41	D
	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE																
_		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.														_		
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  Color coded barrel markings —BOLT SIZE																	
С	SPECIFED PLATE PER MIL - T -16366.											С						
		SUFFIX CAT.NO.WITH "SP" FOR SILVER.																
$\rightarrow$	D	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green  —Wire inspection hole														$\leftarrow$		
В			C U		Rol	HS SPEC			∯ H ∮	eveled wire entr	В		)					В
																		_
							HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.											
Α					_			WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00	24-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	ards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE NTS							<b>A</b> -	PROJECTION	
ı	REV	DATE	DWN	CHK		DESCR	IPTION -	ECN		CTRO TIN PLATE	G. NO. <b>1</b>	86-cp275	56 UN	IN	CH -	<b>⊕</b> Ł	$\Box$	
			4				3	$\triangle$		2					1			