			1	_			_			ı					
	THE INFORMATION	4	0 THE DROEDTY OF OUR EST	3	V		2					1			,
	DISCLOSED IN CO	NFIDENCE AND NOT	S THE PROERTY OF CELEST TO BE REPRODUCED, USED (		CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLOSED EXCEP	T FOR WHICH FURNIS	SHED.		DB011243-251	#1 AWG	225/24 #1 Weld	1/2	3.85	2.77	0.80	0.12	1.75	0.46	
D															D
D	NOTE:	ALL DIMEI     SPECIFIEI	NSIONS ARE IN INCHES I												
			3,LA,LB,WP AND J SERIE "UNDERWRITERS INC."												
			WIRES AND FLEX/24 ST		/—BOLT SIZE										
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS														
		OTHERWI WITH "P".	SE SPECIFIED IN THE SU	JFFIX OF THE CAT.NO.											
	MATERIAL:	HIGH CON	IDUCTIVITY WROUGHT (	COPPER											
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE  SPECIFED PLATE PER MIL - T -16366.  SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С			
							\\/ira ina	no otio	a hala						
					-Wire inspection hole										
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 37					H									
	DIE COLOR	= Green				1				-	=	, '			
							I		f			ı			
			,			\B€	eveled wire entr	у	L	,					
В		~(Ui);													В
			3 <b>ROHS</b> 2002/95/EC												
		LISTED WIRE CONNECTORS													
		ZMVV/2/7/8.E513913													
							A			TD 4			ATI	261	
						Hl	JYA®				COF Rd. Zh			_	
		<del>                                     </del>		_			nuyaco.com				Guangz				
Α						TITLE WIRE CONNECTORS AND SO						DFR	ING		Α
					LUGS FOR CODE AND FLEX CABLE										
	00 23-Aug-25	Ruby Feng Sinia	ı Qiu Celestra	Standards Spec. Initialed.	MATERIAL HIGH COMPLICATIVITY PRE NO					SCALE THRID ANGLE PROJECTION					
	REV DATE	<del>                                     </del>		ESCRIPTION	ECN	FINISH			243-251 86-cp276	65	JNIT INC	$-$ 1 $\epsilon$	<b>⊕</b> €	$\exists$	_
		4	1	3	$\triangle$		2	•	p	1	11 44	1			
			I		T					1		·			