				ı							1					
	THE INFORM	4			3	$\overline{}$		2					1			,
	DISCLOSED II	N CONFIDENCE AN	D NOT TO BE F	PROERTY OF CELESTRA REPRODUCED, USED OR		CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLOSED EX	CEPT FOR WHICH	FURNISHED.			DB011434-261	#1 AWG	225/24 #1 Weld	?1/4	2.33	1.39	0.75	0.12	0.75	0.45	
D																D
D	NOTE:		. DIMENSION ECIFIED.	S ARE IN INCHES UN												
				B,WP AND J SERIES		" FOR USE										
				ERWRITERS INC." AI S AND FLEX/24 STRA		/—BOLT SIZE										
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS															
		OTI		ECIFIED IN THE SUFI												
	MATER	AL: HIG	H CONDUCT	IVITY WROUGHT CO	PPER											
С	FINISH:	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С			
								-Wire ins	pectio	n hole						
\rightarrow	INSTAL DIE COI	ATION GUIDE					H		В	→		A				\leftarrow
		OR = Green							1	 	-		Ψ \ 	_		
							\			1	-		' '			
							∖Be	eveled wire entr	У)					
В			<u> </u>	V					,							В
		c (L) US	RoHS												
		LIS	TED													
			NECTORS 8.E513913													
							ш	JYA®	C	ELES						
								luyaco.com		6. Hua anyu D					n.	
А								-								٨
A						WIRE CONNECTORS AND SOLDERII									Α	
						LUGS FOR CODE AND FLEX CABLE										
	00 23-Au	g-25 Ruby Feng	Sinia Qiu	Celestra St	tandards Spec. Initialed.	itialed. MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER DB011434-261					S	cale NT		D ANGLE PR	OJECTION	
	REV DA	TE DWN	CHK	DES	SCRIPTION	ECN	FINISH		G. NO. 1	86-cp276	58 U	NIT IN		$\bigoplus \Box$	\dashv	
		4			3	\triangle		2			i		1			
				ı							'					