	_		4				3	+		2					1			
ı		HE INFORMATION	VEIDENCE AND	NOT TO BE				CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	'
Г		ISLOSED EXCEPT	FOR WHICH I	FURNISHED.				WP011458-008	#1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223		2.31	1.15	0.68	0.11	0.625	0.41	D
		NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE																
_		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". Color coded barrel markings —BOLT SIZE																
		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
(FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
_	\geqslant	INSTALLATIO								——A——								4
		DIE CODE = DIE COLOR :							/-Wire inspection hole									
E	3		C U		Rol	HS JEC			H H Be	eveled wire entr	В)					В
_																		_
	\vdash												TDA	00:	2021	> A T ! 4	211	1
							HUYA® 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.											
A	\ -								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
		00 23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	ards Spec. Initialed.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTIC WROUGHT COPPER WP011458-008 NTS									ROJECTION	
1	R	EV DATE	DWN	СНК		DESCR	IPTION	ECN	FINISH		2 110	86-cp277	'2 UN	JIT	CH -	(E		
	_		4				3	\uparrow		2					1			