	•		4				3	\downarrow		2					1			
ı		INFORMATION ON THIS DRAWING IS THE PR LOSED IN CONFIDENCE AND NOT TO BE REI						CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C +0.04	D ±0.015	G ±0.02	H ±0.01	'
D	DISLO	SED EXCEPT	FOR WHICH I	FURNISHED.				LB011458	#1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223			1.58	0.67	0.11	0.625	0.41	D
	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE																
_		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. -													_			
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". Color coded barrel markings —BOLT SIZE																	
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE COPPOSITION PLATE DEPO MILL T. 40222												С					
		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.																
	D	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green Wire inspection hole													\leftarrow			
В			C U		Rol	/ HS			H H Be	eveled wire entr	В							В
																		_
								HUYA® Www.huyaco.com CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.										
Α								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
		23-Aug-25	-				ards Spec. Initialed.		WROUGHT COPPER LB011458 NTS			RID ANGLE PE	OJECTION					
1	REV	DATE	DWN	CHK	1	DESCR		ECN		CTRO TIN PLATE	j. NO. 1	86-cp277	4 UN	IN:		Ψ -		
	•		4				3	4		2					1			