	•		4				3	<b>\psi</b>		2					1			
I	DISCL	OSED IN CON	VEIDENCE AND	NOT TO BE		F CELESTRA, IS ED, USED OR		CELESTRA CAT.NO	WIRE SIZE CODE FLEX		BOLT SIZE	A ±0.06	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	'
D	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.			_	LB015678-250	#1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223			1.64	0.70	0.11	0.88	0.42	D
	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE																
_		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.													_			
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  Color coded barrel markings —BOLT SIZE																	
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER  FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE													С				
C		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												C				
	D	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green  Wire inspection hole													$\leftarrow$			
В			C U		Rol-	<b>IS</b>			H PB6	eveled wire entr	В————————————————————————————————————		)					В
_																		_
								HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.										
А								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	rds Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. LB015678-250 SCALE NTS THRID ANGLE PROJ						ROJECTION	NC		
I	REV	DATE	DWN	CHK		DESCR		ECN		CTRO TIN PLATE	G. NO. 1	86-cp278	32 UN	IN:	CH	<b>⊕</b> Ł		
			4		1		3	4		2					1			