	_		4		ı		3	+		2					1			
ı		E INFORMATION CLOSED IN CO				OF CELESTRA, IS		CELESTRA		RE SIZE	BOLT	Α	В	C	D . 0 0 1 5	G	H - 0.04	
C	DIS	LOSED EXCEP				, 33.23 011		CAT.NO LB011458P-250	#1 AWG	FLEX  75 Navy #2 Weld  150/24 = 60.5 kcmil 175/24 =  70.6 kcmil  133/.0223	SIZE		1.26	0.70	0.11	±0.02	±0.01 0.42	D
L		NOTE:		DIMENSION CIFIED.	IS ARE IN	INCHES UNLESS	OTHERWISE			1007.0220								D
_		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.													_			
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  Color coded barrel markings —BOLT SIZE																	
		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
C		FINISH:  ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
	>	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green  Wire inspection hole												$\leftarrow$				
B	3		C U		Rol- 2002/98	HS.		l	∯ H ∮ Be	eveled wire entr	В <u> </u>							В
_																		_
										JYA® nuyaco.com	7	ELES 6. Huar anyu D	ncun F	Rd. Zh	nongci	ın Tow		
Д								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standar	rds Spec. Initialed.		WROUGHT COPPER LB011458P-250 NTS								OJECTION	
ı	RE	V DATE	DWN	CHK		DESCRI		ECN		TRO TIN PLATE	<sup>3. NO.</sup> 1	86-cp278	5 UN	IN		<b>⊕</b> Ł	$\Box$	
	_		4				3	4		2					1			