		4		3		3	\downarrow	2					1										
I	DISCL	OSED IN COM		D NOT TO BE I		OF CELESTRA, IS CED, USED OR		CELESTRA CAT.NO	W CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01]					
D								LB015678P-250	#1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	5/16	3.25	1.64	0.70	0.11	0.88	0.42	D					
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.]							
			LIST	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																			
			OTH			" HAS NOT PEI IN THE SUFFIX	-Color coded barrel markings BOLT SIZE																
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER													с									
С	C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.																						
\rightarrow	D	ISTALLATIC IE CODE = IE COLOR =	37				←Wire inspection hole										\leftarrow						
В				Dus	Rol	HS			↓ ////(H ↓ /////		B					\geq		в					
					2002/3	uleo.			∖—Bo	eveled wire entr	У												
			ZM///2/7/8															_					
A										JYA®						RATIO		-					
										nuyaco.com	76. Huancun Rd. Zhongcun T Panyu Dist. Guangzhou 51149												
								Image: Wire connectors and soldering A LUGS FOR CODE AND FLEX CABLE A															
			Ruby Feng				dards Spec. Initialed.		WR		LB0156	78P-250		CALE NT	S		ROJECTION						
I	REV	DATE	DWN	СНК	<u> </u>	DESC	RIPTION	ECN		CTRO TIN PLATE	G. NO. 18	36-cp278	88 UN	NIT IN(сн 🔤	Ф-E]					
			4				3	4		2					1								