	-		4		1		3	+		2					1			
ı			ON THIS DRA			F CELESTRA, IS D, USED OR		CELESTRA CAT.NO	WIRE SIZE CODE FLEX		BOLT SIZE	A ±0.06	B MIN	C +0.04	D ±0.015	G +0.02	H ±0.01	'
D		OSED EXCEPT	FOR WHICH	FURNISHED.]	LB013801P-250		75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223			1.83	0.70	0.11	1.00	0.42	D
_		IOTE:	SPE	CIFIED.		NCHES UNLESS						1	'		•			_
_		2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". Color coded barrel markings —BOLT SIZE																
С	l _	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.											С					
			SUF	FIX CAT.NC).WITH "SP	' FOR SILVER.			V	Δ	G>							
	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green Wire inspection hole												\leftarrow					
В			UL US ISTED RE CONNECTORS WOODTH	RoHS	l			I	∯ H ∮ Be	eveled wire entr	В <u> </u>)					В
																		_
								CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495. WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
А																		
	00	01-Dec-25	Ruby Feng	Sinia Qiu		Celestra Standar	rds Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJUCTIVITY WROUGHT COPPER LB013801P-250 NTS								ROJECTION	
ı	REV	DATE	DWN	СНК		DESCRI		ECN		TRO TIN PLATE	^{G. NO.} 1	86-cp278	9 ^{UN}	IN IN	CH +	(\exists	
	_		4				3	\triangle		2					1			