	_		4				3	+		2					1								
ı			E INFORMATION ON THIS DRAWING IS THE PROEF CLOSED IN CONFIDENCE AND NOT TO BE REPRO					CELESTRA CAT.NO	WIRE SIZE BOLT A		B MIN	C	D ±0.015	G .0.02	H ±0.01	] '							
ı		DISLOSED EXCEP						LB011243-260	#1 AWG	FLEX  75 Navy #2 Weld  150/24 = 60.5  kcmil 175/24 =  70.6 kcmil  133/.0223			2.83	0.81	0.12	1.75	0.41	D					
		NOTE:  1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.  2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE																					
-		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".														_							
(	C	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER  FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С										
	$\Rightarrow$	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green  Wire inspection hole H											$\leftarrow$										
ı	3	Beveled wire entry  Beveled wire entry												В									
-	$\dashv$																	_					
Α	-							HUYA® Www.huyaco.com  CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.															
	4 <u> </u>							WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE															
			Ruby Feng	<del>                                     </del>			rds Spec. Initialed.			H-CONDUCTIVITY PRT.	LB011	243-260		ALE NT	rs -	ID ANGLE PR	ROJECTION						
	L	REV DATE	DWN 4	CHK		DESCRI	TION 3	ECN	ELEC	TRO TIN PLATE	· NO. 1	86-cp279	1   01	IN(	СН <u>  '</u>	₩ <u> </u>		J					
	_		•		I		-	7					ı		•								