	-		4				3	\rightarrow		2					1			
ı	DISCL	OSED IN CON	VEIDENCE AND	NOT TO BE		F CELESTRA, IS ED, USED OR		CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C +0.04	D ±0.015	G +0.02	H ±0.01	'
D	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.			J	LB011243-260	#1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223			2.83	0.81	0.12	1.75	0.41	D
	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE																
_	-	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. -													_			
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". Color coded barrel markings —BOLT SIZE																	
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE												С					
O		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												J				
	D	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green Wire inspection hole													\leftarrow			
В			C U		Rol- 2002/96	/ HS			H Be	eveled wire entr	В)					В
_	-																	_
								HUYAR CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.										
Α								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
		23-Aug-25	Ruby Feng				rds Spec. Initialed.		WR	OUGHT COPPER		243-260		ale NT		ID ANGLE PR	OJECTION	
ı	REV	DATE	DWN	CHK		DESCR		ECN		CTRO TIN PLATE	G. NO. 1	86-cp279)1 UN	IN(ψ L		
	-		4		1		3	4		2					1			