			4				3	\psi		2					1			
ı	DISCL	OSED IN CON	NFIDENCE AND	NOT TO BE		OF CELESTRA, IS ED, USED OR		CELESTRA CAT.NO	W CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C +0.04	D ±0.015	G +0.02	H ±0.01	'
D	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				LB011243P-260		75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223			2.83	0.83	0.12	1.75	0.41	D
	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE													_			
_		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. -														_		
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". Color coded barrel markings —BOLT SIZE																	
С		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE ODEOUSED BLATE DED MILL T. 19999												С				
		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.																
	D	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green Wire inspection hole														\leftarrow		
В			C U		Rol	HS HS			H †	eveled wire entr	В)					В
_																		_
								HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.										
Α								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00	24-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	ards Spec. Initialed.		WR	OUGHT COPPER	DPPER LB011243P-260 NTS					OJECTION	ECTION	
ı	REV	DATE	DWN	CHK		DESCR	IPTION	ECN		CTRO TIN PLATE	9. NO. 1	86-cp279	05 UN	IN IN		⊕ Ł	\supset	
			4				3	\triangle		2					1			