	•		4				3	\downarrow		2					1			
ı	DISCL	OSED IN CON	VEIDENCE AND	NOT TO BE		OF CELESTRA, IS ED, USED OR		CELESTRA CAT.NO	W CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C +0.04	D ±0.015	G +0.02	H ±0.01	'
D	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				LB011458P-260		75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223			1.27	0.67	0.1	0.63	0.41	D
	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE																
_		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.													_			
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". Color coded barrel markings —BOLT SIZE																	
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE												С					
C		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.													C			
	D	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green Wire inspection hole													\leftarrow			
В			C U		Rol	HS.			H PB6	eveled wire entr	В)					В
_																		_
							HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.											
А								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
		24-Aug-25	Ruby Feng				ards Spec. Initialed.		WR		LB0114	58P-260	\bot	ale NT		ANGLE PF	OJECTION	
ı	REV	DATE	DWN	СНК	1	DESCR	IPTION	ECN		TRO TIN PLATE	G. NO. 1	86-cp279	06 UN	IN(⊕ Ł		
	•		4				3	4		2					1			