		4		3		\downarrow	2				1				
I	DISCLOSED IN	CONFIDENCE AN	ID NOT TO BE REF	DERTY OF CELESTRA, IS PRODUCED, USED OR		CELESTRA CAT.NO	W CODE	IRE SIZE FLEX	BOLT A SIZE ±0.0	B 6 MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
D	DISLOSED EX	CEPT FOR WHICH	FURNISHED.			LB011434P-260	#1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	?1/4 3.02	1.39	0.67	0.10	0.75	0.41	D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														
		LIS	TED BY "UNDEF	VP AND J SERIES OF RWRITERS INC." AND AND FLEX/24 STRANE	"CSA" FOR USE										
		OTI		/ITH "L" HAS NOT PEI IFIED IN THE SUFFIX	Color coded barrel markings BOLT SIZE										
	MATERI	AL: HIG	H CONDUCTIV	TY WROUGHT COPP											
С	C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.														
							<	——A	→						
\rightarrow	DIE COD	ATION GUIDE E = 37 OR = Green				Wire inspection hole									
В			DUS TED NECTORS REF13913	RoHS	H Beveled wire entry										
															_
										CTDA			ΟΛΤΙΛ		
								JYA® nuyaco.com	76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.						
А						WIRE CONNECTORS AND SOLDERING									
					LUGS FOR CODE AND FLEX CABLE										
		-25 Ruby Feng	+		MATERIAL HIGH-CONDUCTIVITY wrought copper PRT. NO. LB011434P-260 COUDTION ECNI FINISH DWG. NO. COUDTION										
1	REV DAT	E DWN 4	СНК	DESC	RIPTION 3	ECN	ELE	CTRO TIN PLATE	^{5. NO.} 186-cp	2797 ⁰ I	INC	CH 1	ΨĽ		l
	_ 4 3					4		۷		I		I			