	-		4				3	$\downarrow$		2					1			
ı	DISCL	OSED IN CON	VEIDENCE AND	NOT TO BE		F CELESTRA, IS ED, USED OR		CELESTRA WIRE		RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C +0.04	D ±0.015	G -0.02	H ±0.01	'
D	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.			_	LB013801P-260		75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223			1.83	0.67	0.10	1.00	0.41	D
	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE																
_		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES													_			
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  Color coded barrel markings BOLT SIZE																	
0	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER  FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE																	
С		SPECIFED PLATE ONLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С				
	D	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green  Wire inspection hole													$\leftarrow$			
В			C U		Rol- 2002/95	/ IS		I	H Be	eveled wire entr	В————————————————————————————————————		)					В
_	-																	_
								CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.  TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
А																		
		23-Aug-25					rds Spec. Initialed.		WR	H-CONDUCTIVITY PRT	LB0138	01P-260		ALE NT		ANGLE PF	OJECTION	
ı	REV	DATE	DWN	CHK	1	DESCR		ECN		CTRO TIN PLATE	9. NO. <b>1</b>	86-cp279	)8 UN	IN(		<b>⊕</b> Ł		
	-		4				3	4	,	2					1			