		4		3	$\overline{}$	2						1		,
			THE PROERTY OF CELESTR BE REPRODUCED, USED O		CELESTRA CAT.NO		RE SIZE	BOLT SIZE			D .04 ±0.0	G 15 ±0.02	H ±0.01	
	DISLOSED EXCEP	T FOR WHICH FURNISHI	ED.		LB015601P-251	CODE #1 AWG	FLEX 225/24 #1 Weld				76 0.12		0.46	
D	NOTE:	4 ALL DIMENS	IONE ARE IN INCHES I	INILESS OTHERWISE										D
	NOTE.	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.												
		2. ALL DA,DB,L	,	Color coded barrel markings										
			UNDERWRITERS INC." . IRES AND FLEX/24 STR	/_BOLT SIZE										
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS													
			SPECIFIED IN THE SU											
		WITH "P".			T.NO.									
	MATERIAL:	HIGH COND	UCTIVITY WROUGHT C	OPPER										
С	FINISH:		N PLATE UNLESS OTH		⊸-G-⊸								С	
			.NO.WITH "SP" FOR SIL			A								
	—Wire inspection hole													
\rightarrow	INSTALLATIO			B B									\leftarrow	
	DIE CODE = 37 DIE COLOR = Green								Y			7		
									<u> </u>			\pm)		
						\Be	veled wire entr	v	D					
В		Develed wife entry											В	
D		c(VL)us	RoHS											
		LISTED	ZWZISIEC											
		WIRE CONNECTORS ZMVV/2/7/8.E513913												
														<u> </u>
								CE	LEST	RA C	ORPO	RATIO	ON	
							JYA®					cun Tow		
						www.h	uyaco.com	Pá	anyu Dis	t. Guar	ngzhou	511495.		
Α					WIRE CONNECTORS AND SOLDERIN								Α	
				LUGS FOR CODE AND FLEX CABLE										
	00 23-Aug-25	Ruby Feng Sinia C	tiu Celestra	Standards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE WROUGHT COPPER LB015601P-251 NTS							ROJECTION	
	REV DATE	DWN CH		ESCRIPTION	ECN	EINISH			86-cp2803	UNIT	INCH	(\exists	
		4		3	\triangle		2		-			1		
			ı							ı				