				ı		4					1					
	THE INFORM	4	AVAILAGE TELE		3	V	10.0	2	I · -		<u> </u>	- 1	1	_		,
	DISCLOSED I	N CONFIDENCE AN	D NOT TO BE F	PROERTY OF CELESTRA REPRODUCED, USED OR		CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLOSED E	CEPT FOR WHICH	FURNISHED.			LB015678P-261	#1 AWG	225/24 #1 Weld	5/16	3.21	1.58	0.75	0.12	0.88	0.45	
D																D
D	NOTE:	1. ALL SPE														
				B,WP AND J SERIES												
				DERWRITERS INC." A S AND FLEX/24 STRA		BOLT SIZE										
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS															
		OTI			FIX OF THE CAT.NO.											
	MATER	AL: HIG	H CONDUCT	IVITY WROUGHT CO	PPER											
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE  SPECIFED PLATE PER MIL - T -16366.  SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С				
								-Wire ins	pectio	n hole			1			
$\rightarrow$	INSTAL DIE CO	LATION GUIDE				,	1		В	<b>→</b>		A				$\leftarrow$
		OR = Green				'	1				-		Ψ \ 	_		
							<b>\</b>		Ī	1	-		<del>'   '</del>			
							\Вє	eveled wire entr	У		)					
В			<u> </u>	<b>~</b>					,							В
		c (	L) US	ROHS 2002/95/EC												
		LIS	TED													
		WIRE CON ZMVV/2/7.	NECTORS 8.E513913													
							ш	JYA®				COF				
								luyaco.com				Rd. Zh Juangz			n.	
А								-								٨
A						WIRE CONNECTORS AND SOLDERING									Α	
						LUGS FOR CODE AND FLEX CABLE										
	00 23-Au	g-25 Ruby Feng	Sinia Qiu	Celestra S	tandards Spec. Initialed.	ialed.  MATERIAL HIGH-CONDUCTIVITY PRT. NO. SC WROUGHT COPPER LB015678P-261					cale NT		D ANGLE PR	OJECTION		
	REV DA	TE DWN	СНК	DE	SCRIPTION	ECN	FINISH		9. NO. <b>1</b>	86-cp280	09	NIT IN		$\bigoplus \Box$	$\exists$	
		4		1	3	$\triangle$		2			i		1			
				ı							'					