		4			3			$\downarrow$	7	2			1												
I	THE INFORMATION ON THIS DRAWING IS THE						CEL	CELESTRA	WIRE SIZE B			Α	В	C D		G	Н	1							
			FIDENCE AND		REPRODU	CED, USED OR			T.NO	CODE	FLEX	SIZE	±0.06	MIN	-		±0.02	±0.01							
_	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				DB1	101434	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	1/4	2.76	1.81	0.75	0.14	0.75	0.46							
D	D NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																		D						
			LIST	ED BY "UN	DÉRWRIT		CAT.NO.S ARE ) "CSA" FOR USE DED CABLES.																		
			OTH			-" HAS NOT PE IN THE SUFFI)		-BOLT SIZE																	
	М	ATERIAL:	HIGH	H CONDUC	TIVITY W	ROUGHT COPF	PER																		
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.													С											
		ISTALLATIO																							
	D	IE CODE =	42					-Wire inspection hole																	
В	D	IE COLOR :			Ro	HS		H Beveled wire entry																	
			-																						
A											JYA® nuyaco.com	7	<b>ELES</b> 76. Hua Panyu (	ancun	Rd. Zh	nongci	in Tow								
									TITLE WIRE CONNECTORS AND SOLDERING										A						
								LUGS FOR CODE AND FLEX CABLE																	
	00	01-Jul-25	Ruby Feng	Sinia Qiu		Celestra Star	ndards Spec. Initiale	ed.		MATERIAL HIG WR	H-CONDUCTIVITY PRT OUGHT COPPER	. NO. DB1	01434	S	CALE N	rs			JECTION						
I	REV	DATE	DWN	СНК		DESC	RIPTION		ECN		CTRO TIN PLATE	<sup>G. NO.</sup> 1	86-cp28	11	NIT IN	СН	ŒE								
			4				3	4	7		2					1									
								1																	