						I									
		4			3	$\overline{}$	2					1			
·				OERTY OF CELESTRA, I PRODUCED, USED OR	S	CELESTRA CAT.NO	CODE	SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01	
	DISLOSED EXCE	PT FOR WHICH F	URNISHED.			CAT.NO	CODE	100 Navy #1	SIZL	±0.00	IVIIIN	±0.04		±0.01	ł
						DA1056-260	1/0 AWG	Weld 225/24 =	5/16	1.83	0.70	0.88	1.16	0.39	
								90.8 kcmil 133/.0254							
D															D
	NOTE:		CIFIED.	ARE IN INCHES UNL	.ESS OTHERWISE		Color coded marking								
		2. ALL	DA,DB,LA,LB,V	VP AND J SERIES O	F CAT.NO.S ARE										
				RWRITERS INC." AN AND FLEX/24 STRAN		Bolt Size									
				VITH "L" HAS NOT PI CIFIED IN THE SUFFI											
		WITH	H "P".			+	U								
	MATERIAL	: HIGH	H CONDUCTIV	ITY WROUGHT COP	PER	Ш		ja 🔰							
С	FINISH:			TE UNLESS OTHER	WISE			D							С
		_	-	PER MIL - T -16366. 'ITH "SP" FOR SILVE	R.		B								
						-		4	-						
\rightarrow		TION GUIDE													4
	DIE CODE					_	T							7	
]-	. R	Inspection	on Hol	e —					
						T F		1					7		
В				_									В		
	ال.		,A NI	EDe3 .	ROHS (E	<u>. </u>					E				
			М	ED3 (JUT HOSEU		Povolo	d optra							
	LIS WIRE C	ONNECTOR					Beveled	a entry							
								√ A® C	ELES	TRA	COF	RPOF	RATIO	NC	
						HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town.									
						www.huyaco.com Panyu Dist. Guangzhou &					hou 5'	11495.			
Α						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
			_												
	00 23-Aug-2	5 Ruby Feng	eng Sinia Qiu Celestra Standards Spec. Initialed.				MATERIAL HIGH-CONDUC WROUGHT CO	CTIVITY PRT. NO.	56-260	SC	CALE N7		RID ANGLE PI	ROJECTION	
	REV DATE		СНК	DES	CRIPTION	ECN	FINISH ELECTRO TIN F	81118 118	86-cp02	83	NIT	CH -	(E	\exists	
		4			3	\triangle	2	-	•			1	·		'
				ı		T				ı					