|               |          |   | 4                     |                      | 1          |                                   | 3                    | +  |  | 2   |                     |          | I        |       | 1      |         |            |                |  |
|---------------|----------|---|-----------------------|----------------------|------------|-----------------------------------|----------------------|--|--|---|---------------------|----------|----------|-------|--------|---------|------------|----------------|--|
|               | THE IN   | IFORMATION  | ON THIS DRA           | WING IS THE          | PROERTY (  | OF CELESTRA, IS                   | <u> </u>             | CELESTRA   | W  | IRE SIZE  | BOLT                | А        | I<br>В   | С     | D      | G       | Н          | 1 <sup> </sup> |  |
|               |          |   | FOR WHICH             |                      | REPRODUC   | ED, USED OR                       |                      | CAT.NO   | CODE   | FLEX  | SIZE                |          | MIN      | ±0.04 | ±0.015 | ±0.02   | ±0.01      | 1              |  |
| -             |          |   |                       |                      |            |                                   |                      | WP101458-179   | 1/0 AWG  | 100 Navy #1<br>Weld 225/24 =<br>90.8 kcmil<br>133/.0254 | ?1/4                | 2.59     | 1.42     | 0.75  | 0.12   | 0.63    | 0.45       |                |  |
| D             | N        | OTE:  |                       | DIMENSION<br>CIFIED. | NS ARE IN  | INCHES UNLESS                     | OTHERWISE            |  |  |   |                     |          |          |       |        |         |            | D              |  |
|               |          | 2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. |                       |                      |            |                                   |                      |  |  |   |                     |          |          |       |        |         |            |                |  |
|               | 1        | PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS  Color coded barrel markings   |                       |                      |            |                                   |                      |  |  |   |                     |          | <b> </b> |       |        |         |            |                |  |
|               |          |   | OTH                   |                      |            | " HAS NOT PEEP<br>IN THE SUFFIX O |                      | BOLT SIZE  |  |   |                     |          |          |       |        |         |            |                |  |
|               | M        | ATERIAL:  | HIGI                  | H CONDUCT            | TIVITY WR  | OUGHT COPPER                      | 2                    | C  |  |   |                     |          |          |       |        |         |            |                |  |
| С             | FI       | NISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.   |                       |                      |            |                                   |                      |  |  |   |                     |          |          |       |        | С       |            |                |  |
|               |          |   | SUF                   | FIX CAT.NC           | ).WITH "SF | P" FOR SILVER.                    |                      |  |  | V   | G                   |          |          |       |        |         |            |                |  |
|               |          |   |                       |                      |            |                                   |                      |  |  |   |                     |          |          |       |        |         |            |                |  |
| $\rightarrow$ |          | ISTALLATIO  |                       |                      |            |                                   |                      |  |  | ∕-Wire ins  | enactio             | n hole   |          |       |        |         |            | $\leftarrow$   |  |
|               |          | IE CODE = 7   |                       |                      |            |                                   |                      |  | 1 8//4   |   | pectio              | ii iiole |          |       |        |         |            |                |  |
|               |          |   |                       |                      |            |                                   |                      |  | H  |   | В                   |          |          |       |        |         |            |                |  |
| В             |          |   | _                     |                      |            |                                   |                      |  |  |   |                     |          |          |       |        | =)      |            | В              |  |
| _             |          | Beveled wire entry  |                       |                      |            |                                   |                      |  |  |   |                     |          |          |       |        |         |            |                |  |
|               |          |   | ISTED<br>E CONNECTORS | 2002/95/EC           |            |                                   |                      |  |  |   |                     |          |          |       |        |         |            |                |  |
|               |          | ZMN   | VV/2/7/8.E513913      |                      |            |                                   |                      |  |  |   |                     |          |          |       |        |         |            |                |  |
|               |          |   | I                     |                      |            |                                   |                      |  | 1  |   |                     |          |          |       |        |         |            |                |  |
|               |          |   |                       |                      |            |                                   |                      | HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town.  |  |   |                     |          |          |       |        |         |            |                |  |
|               |          |   |                       |                      |            |                                   |                      | www.huyaco.com Panyu Dist. Guangzhou 511495.               |  |   |                     |          |          |       | 11.    |         |            |                |  |
| Α             |          |   |                       |                      |            |                                   |                      | WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE |  |   |                     |          |          |       |        |         |            |                |  |
|               |          |   |                       |                      |            |                                   |                      |  |  |   |                     |          |          |       |        |         |            |                |  |
|               | $\vdash$ |   | Ruby Feng             |                      |            |                                   | rds Spec. Initialed. |  | MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER WP101458-179 SCALE NTS |   |                     |          |          |       |        | ANGLE P | PROJECTION |                |  |
| 1             | REV      | DATE  | DWN                   | CHK                  |            | DESCRI                            |                      | ECN  |  | CTRO TIN PLATE  | <sup>G. NO.</sup> 1 | 86-cp284 | 2   "    | IN    | CH ]   | Ψ τ     |            | 1              |  |
|               |          |   | 4                     |                      |            |                                   | 3                    | 4  |  | 2   |                     |          |          |       | 1      |         |            |                |  |