									2			1											
	4			3			∇			-		1				•							
		TION ON THIS DR. CONFIDENCE AN					CELESTRA CAT.NO			BOLT SIZE	A ±0.06	B MIN	C	D	G	H							
		CEPT FOR WHICH]	CAT.NO	CODE	FLEX 100 Navy #1	SIZE	±0.06		±0.04	±0.015	±0.02	±0.01	1						
							LB103843P-250	1/0 AWG	Weld 225/24 = 90.8 kcmil 133/.0254	3/8	4.27	2.58	0.76	0.12	1.75	0.46							
D							L	1	100/.0204		I		I	I			D						
	NOTE:	SPECIFIED.																					
		LIS	TED BY "UN	DERWRITER	SERIES OF CA S INC." AND "C /24 STRANDED	SA" FOR USE																	
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																					
		OTH			THE SUFFIX OF																		
	MATERI	L: HIG	H CONDUC	TIVITY WROL	JGHT COPPER																		
С	FINISH:				SS OTHERWISE	E																	
	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.																						
	G																						
													\triangleleft										
	DIE CODE = 42								-Wire ins	pectio	n hole						\neg						
	DIE COLOR = Pink																						
										\sum													
р																							
В	CULUS ROHS D										B												
		LIS WIRE CON ZMVV/2/7/	NECTORS 8.E513913																				
										С	ELES	STRA		RPOF	RATIO	ON	1						
									JYA®	7	76. Hua	ancun	Rd. Zh	nongcu	in Tow								
							www.huyaco.com Panyu Dist. G							Guangzhou 511495.									
A					WIRE CONNECTORS AND SOLDERING									A									
								LUGS FOR CODE AND FLEX CABLE															
	00 23-Aug	-25 Ruby Feng	sinia Qiu	С	elestra Standar	ds Spec. Initialed.		MATERIAL HIG WR	H-CONDUCTIVITY PRT DUGHT COPPER	. NO. LB1038	343P-250) S	CALE N	TS	ND ANGLE PF	ROJECTION							
	REV DAT	e dwn	СНК		DESCRIF	PTION	ECN	FINISH		2. NO	86-cp28		NIIT		Ф£								
	· · · · ·	4				3	\square		2					1			-						
L				I			I					ſ											