	•									工									
	THE WES		4			05.051.507		3		\bigvee	 	2	1	<u> </u>		1		1	,
	DISCLOSE	D IN CONFIG	DENCE AND	WING IS THE NOT TO BE F						CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	+0.06	B MIN	C ±0.04	R	1D ±0.01	
	DISLOSEL	EXCEPT FC	OR WHICH I	FURNISHED.						DA1012-251	1/0 AWG	275/24 1/0 Weld	1/2	2.06	1.09	0.85	1.00	0.45	1
D	NOTI	≣ :		DIMENSION CIFIED.	S ARE IN	N INCHES	UNLESS	OTHERWIS	SE	Color coded marking Bolt Size									
			LIST ON (PRE	DA,DB,LA,LI ED BY "UND CODE WIRE -FIX CAT.NO ERWISE SP H "P".	DERWRIT S AND FI D.WITH "I	TERS INC. LEX/24 ST L" HAS NC	" AND "CS "RANDED)T PEEP I	SA" FOR US CABLES. HOLE UNLE	SE ESS	HUYA®									
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER											В							
С	FINIS	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								A									С
→	DIE (INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink								R Inspection Hole									
В		LISTED		A N	IEB	S 3	RoHS		E	1.]	Bev	eled entry			<i>(</i>				В
		WIRE CONNECT	OR																
	1																		-
											HU www.huy	YA	ELES 76. Hua Panyu	ancun	Rd. Zh	nongci	un Tov	vn.	
А											WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	00 23-	Aug-25 R	uby Feng	Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CO WROUG	NDUCTIVITY PRT. NO. IT COPPER DA1	012-251	S	CALE N	TS TH	RID ANGLE	PROJECTION	1
	REV [DATE	DWN	СНК			DESCRIF	PTION		ECN	FINISH	8146.446	186-cp02	.87 U	INIIT	СН	O		
		,	4	'				3		4	2	•				1			