THE INFORMATION ON THIS DRAWING IS THE PROBERTY OF CELESTRA, IS DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISCLOSED IN CONFIDENCE AND THE SUFFIX OF THE CAT.NO.  DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISCLOSED IN CONFIDENCE AND THE WHICH FURNISHES SPECIFIED.  1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.  2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER  C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL. "T. 1-6366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.  INSTALLATION GUIDE DIE CODE = 42  DIE COLOR = Pink  WIRE SIZE  BOLT A B BULT A B BULT A B BULT A B BULT A BOLT AND WHICH TO THE WHICH THE AND THE WHICH THE ALL THE AND THE ALL T	04 ±0.015 ±0.02 ±0.01	D
DISLOSED EXCEPT FOR WHICH FURNISHED.    Dislosed Except for Which Furnished.   Court   100 Navy #1   Weld 225/24 = 90.8 kcmil   133/.0254   21/2   4.46   2.83   0.8   2.83		D
D  NOTE:  1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.  2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWIRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  MATERIAL:  HIGH CONDUCTIVITY WROUGHT COPPER  C  FINISH:  ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.  Wire inspection hole  Weld 225/24 = 90.8 kcmii 133/.0254  21/2 4.46 2.83 0.8	33 0.11 1.75 0.45	D
NOTE:  1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.  2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER  FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.  Wire inspection hole		
LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.  INSTALLATION GUIDE DIE CODE = 42  Wire inspection hole		
PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER  FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.  INSTALLATION GUIDE DIE CODE = 42  Wire inspection hole		
OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER  FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.  INSTALLATION GUIDE DIE CODE = 42  Wire inspection hole		
C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.  INSTALLATION GUIDE DIE CODE = 42  Wire inspection hole		
SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.  INSTALLATION GUIDE DIE CODE = 42  Wire inspection hole		
INSTALLATION GUIDE DIE CODE = 42  Wire inspection hole		С
DIE CODE = 42 /- Wire inspection hole		
DIE CODE = 42 /- Wire inspection hole		
DIE COLOR = Pink		$\leftarrow$
H H B		
B C RoHS, Beveled wire entry		В
LISTED		
WIRE CONNECTORS ZMVV/2/7/8.E513813		
		<del></del>
	ORPORATION	
76. Huancun Rd. www.huyaco.com Panyu Dist. Guan		
A TITLE WIRE CONNECTORS AND SO		Α
LUGS FOR CODE AND FLEX		
00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.  MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER LB101243P-260	NTS THRID ANGLE PROJECTION	
REV DATE DWN CHK DESCRIPTION ECN FINISH ELECTRO TIN PLATE DWG. NO. 186-cp2873	INCH	1
4   3   2	1	