	_		4		1		3	3	+		2					1				
ı	THE I	NFORMATION	I ON THIS DRA	WING IS THE	PROERTY (DF CELESTRA, IS			CELESTRA		RE SIZE	BOLT	A	В	C	D	G	Н]	
			FOR WHICH						CAT.NO	CODE	FLEX 100 Navy #1	SIZE	±0.06	MIN	±0.04	±0.015	±0.02	±0.01	-	
_									LB101401P-260	1/0 AWG	Weld 225/24 = 90.8 kcmil 133/.0254	?1/4	3.27	1.64	0.75	0.12	1.00	0.45		
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																		D	
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 																		
_	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. Color coded barrel markings —BOLT SIZE																			
		WITH "P".									/									
		MATERIAL:				OUGHT COPP														
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.																		
										—	A	G								
	NSTALLATION GUIDE																			
		DIE CODE =	42							-Wire inspection hole										
		DIE COLOR = PINK H										\								
D						/				1					\in		\Rightarrow		 	
В		CUL) US ROHS DEveled wire entry										В								
			LIST WIRE CONN																	
			ZMVV/2/7/8	.E513913																
										ы	JYA®		ELES							
										76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.								n.		
Α										- TITLE WIRE CONNECTORS AND SOLDERING A									Α	
								LUGS FOR CODE AND FLEX CABLE												
	00	23-Aug-25	Ruby Feng	by Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE LB101401P-260 NTS								PROJECTION		
1	REV	DATE	DWN	СНК		DESC	RIPTION	V	ECN		CTRO TIN PLATE	G. NO. 1	86-cp287	'6 U	IN	CH	⊕ Ł	\exists] ,	
	_		4				3		\triangle		2					1				