		4		3	∇	2				1	<u> </u>			
·			S THE PROERTY OF CELE TO BE REPRODUCED, USE		CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE		B C /IIN ±0.		G ±0.02	H ±0.01	•
	DISLOSED EXCEP	T FOR WHICH FURNIS	HED.		LB101243P-261	1/0 AWG	275/24 1/0 Weld			.83 0.8	_		0.48	
						·				I	!			
_														_
D	NOTE:	1 ALL DIMEN	ISIONS ARE IN INICHE	SOLINII ESS OTHEDWISE										D
	NOTE.	E: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.												
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S AREColor coded barrel markings												
			"UNDERWRITERS IN WIRES AND FLEX/24		/_BOLT SIZE									
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS													
		OTHERWIS		SUFFIX OF THE CAT.NO.										
		WITH "P".												
	MATERIAL:	HIGH CON	DUCTIVITY WROUGH	T COPPER										
С	FINISH:		TIN PLATE UNLESS C			⊸-G-⊸								
	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.													
	—Wire inspection hole													
\rightarrow	INSTALLATI				B B									
	DIE CODE = 42 DIE COLOR = Pink							7			7			
												<u> </u>		
						\Re	veled wire entry	v	Ď					
В		Develed wife entry											В	
D		c(VL)u	S RoHS											D
		LISTER	2002/95/EC											
		WIRE CONNECTORS ZMVV/2/7/8.E513913												
								CE	LEST	RA C	ORPO	RATIO	NC	
							JYA®	76	6. Huand	cun Rd.	Zhongc	un Towi		
_						www.h	uyaco.com	Pa	anyu Dis	st. Guan	gzhou 5	511495.		
Α					TITLE WIRE CONNECTORS AND SOLDER								Α	
						LU	JGS FOR C	R CODE AND FLEX CABLE						
	00 23-Aug-25	Ruby Feng Sinia	Qiu Celes	stra Standards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID. WROUGHT COPPER LB101243P-261 NTS							OJECTION	
	REV DATE	 	HK Section	DESCRIPTION	ECN	EINIISH			6-cp2888	UNIT	INCH	⊕ €	\exists	_
		4	<u> </u>	3	$\overline{}$		2		, ,,,,,		1	 		
			I		\top					ı				