	•				1							1					
			4				3		2			<u> </u>		1			.
	DISCLOSE	O IN CONFIE	DENCE AND	NOT TO BE F		F CELESTRA, IS ED, USED OR		CELESTRA CAT.NO	CODE	SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01	
	DISLOSED	EXCEPT FO	OR WHICH I	FURNISHED.				CAT.NO	CODE	100 Navy #1	SIZL	±0.00	IVIIIN	±0.04		±0.01	ł
								DA1038-252	1/0 AWG	Weld 225/24 =	3/8	1.74	0.83	0.76	0.94	0.39	
								2711000 202	.,,,,,,,,	90.8 kcmil 133/.0254	0,0		0.00	""	0.0 .	0.00	
D												<u> </u>	l	<u>I</u>	<u> </u>	ļ.	D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																
								Color coded marking									
						J SERIES OF C RS INC." AND "		Bolt Size									
						X/24 STRANDE			/								
			PRE	-FIX CAT.NC	D.WITH "L"	HAS NOT PEEF	P HOLE UNLESS	_		()		+					
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															
									SE C	1 2		ار					
	MATE	RIAL:	HIGH	H CONDUCT	IVITY WR	DUGHT COPPE	R	L				•					
С	FINIS	H:				ESS OTHERWIS	SE								(С	
	SPECIFED PLATE SUFFIX CAT.NO.W									В	-						
								-		4	-						
	INST	ALLATION	GUIDE														
	DIE C	ODE = 42															
	DIEC	OLOR = P	ink					1-	R	Inspecti	on Hol	е					
															_		
															\rightarrow		
В			•	A		- 2 L									В		
	ا ا	:(ŲL)u	is 📑	: N	IFR	C 5 Roll							(-			
		LISTED	4						Beveled	d entrv							
		WIRE CONNECTO	OR														
]																l
										Z A R C	ELES	STRA	COI	RPOI	RATIO	NC	
									HUYA			76. Huancun Rd. Zhongcun Town.					
									www.huyaco.com P		Panyu Dist. Guangzhou 511495.						
Α						_	TITLE WIRE CONNECTORS AND SOLDERING								Α		
									LUGS FOR CODE AND FLEX CABLE								
		A 25 D 5 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0							MATERIAL HIGH-CONDU		_ / \ \		CALE		RID ANGLE PI	ROJECTION	
	00 23-Aug-25 Ruby Feng Sinia Qiu					Celestra Standards Spec. Initialed.			WROUGHT COPPER DA1038-252						NTS A		
1	REV D	ATE	DWN	CHK		DESCR	IPTION	ECN	ELECTRO TIN F	PLATE DVVG. NO. 1	86-cp02	90	IN	CH	\(\psi\)		J _I
			4				3	4	2					1			
								ı									