				1		<u></u>				i					
		4 3 $\sqrt{}$ 2				<u> </u>		1							
•			AWING IS THE PROB ID NOT TO BE REPR	ERTY OF CELESTRA, IS		CELESTRA	WIRE		BOLT	A	В	C	R	ID	·
		CEPT FOR WHICH		000000, 0000 011		CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	±0.04		±0.01	-
						DA1038-252	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	3/8	1.74	0.83	0.76	0.94	0.39	
D											ı				D
	NOTE:		_ DIMENSIONS AF ECIFIED.	RE IN INCHES UNLE	SS OTHERWISE	Color coded marking									
					ES OF CAT.NO.S ARE										
				VRITERS INC." AND ID FLEX/24 STRAND	Bolt Size										
		OT		TH "L" HAS NOT PEE FIED IN THE SUFFIX	DIE COLOR										
	MATER	AL: HIC	H CONDUCTIVIT	Y WROUGHT COPPI											
С	FINISH	SP	ECIFED PLATE PI	E UNLESS OTHERW ER MIL - T -16366. 'H "SP" FOR SILVER.	B A									С	
						,									
\rightarrow		_ATION GUIDE													4
		DE = 42 _OR = Pink										7			
]-	- R	Inspecti	on Hol	e					
В		(()) ₁₁₈ •	<u>v</u> ≜ nfe	s3 👟 (C F						E				В
		LISTED	A NEL				Beveled	d entry							
		WIRE CONNECTOR													
															 —
		<u> </u>						A -	FI = 6		00:	200	- A		
							HUY		ELES					_	
												76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.			
Α										, ,					
, ,							WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	00 01-De	c-25 Ruby Fen	Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				MATERIAL HIGH-CONDUC WROUGHT CO)38-252	S	CALE N		RID ANGLE PI	ROJECTION	
	REV DA		CHK		RIPTION	ECN	FINISH ELECTRO TIN F	81110 110	86-cp02	90	NIIT	CH -	D E	\exists	
		4	1		3	<u> </u>	2		-			1			'
				•		I				•					