													ı						
	THE INE	4 THE INFORMATION ON THIS DRAWING IS THE PROEF		DDOEDTV	·		3	V OFFI FOTDA	2 WIRE SIZE		DOL T			1	1	T .5	,		
	DISCLOS	SED IN CON	FIDENCE AN	ID NOT TO BE FURNISHED.					CELESTRA CAT.NO	CODE	FLEX	BOLT SIZE	±0.06	B MIN	C ±0.04	R	1D ±0.01		
	DISLOSE	D LAGLET	TOR WITICI	TORNISTIED.					DA1012-261	1/0 AWG	275/24 1/0 Weld	1/2	2.02	1.08	0.83	0.97	0.44]	
D	NOT	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE								Color coded marking Bolt Size									
_		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								DIE COLOR OIE COLOR C									
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER									В	-								
С	FINI	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							A									С	
→	DIE	INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink							R Inspection Hole									\leftarrow	
В	Beveled entry LISTED Beveled entry														В				
		WIRE	CONNECTOR																
	1																	_	
										HUY www.huyac	A	ELES 76. Hua Panyu I	ancun	Rd. Zh	nongci	un Tov	vn.		
А										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
	00 14	4-Dec-25	Ruby Feng	Sinia Qiu		Celestra S	Standards	Spec. Initialed.		MATERIAL HIGH-CONDU WROUGHT C	JCTIVITY PRT. NO. OPPER DA10	12-261	S	CALE N		RID ANGLE	PROJECTION	1	
ı	REV	DATE	DWN	СНК		DE	SCRIP	TION	ECN	FINISH ELECTRO TIN	81118 118	86-cp02	92	NIIT	СН	(,	
		'	4					3	\uparrow	2	•		ĺ		1				