					1									
		4		3	\bigvee	2					1			
'			HE PROERTY OF CELESTRA BE REPRODUCED, USED OF		CELESTRA CAT.NO		RE SIZE	BOLT SIZE	A ±0.06 N		C D	G 15 ±0.02	H ±0.01	
		T FOR WHICH FURNISHE			DB301243-261	CODE 3/0 AWG	FLEX 450/24 3/0 Weld	?1/2			03 0.1		0.63	l
_														_
D	NOTE:	1 ALL DIMENSI	ONS ARE IN INCHES U	NI ESS OTHERWISE										D
	SPECIFIED.													
			A,LB,WP AND J SERIES	Color coded barrel markings BOLT SIZE										
			INDERWRITERS INC." A RES AND FLEX/24 STR											
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS													
		OTHERWISE WITH "P".	SPECIFIED IN THE SUF	FFIX OF THE CAT.NO.	NO.									
	MATERIAL													
		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE											С	
С	FINISH:	SPECIFED PI	ATE PER MIL - T -1636											
		SUFFIX CAT.	NO.WITH "SP" FOR SIL	VER.			~							
							∕-Wire ins	enection	hole					
_	15.10.7.1.1.4.7.1	ON OURDE			 		pedion	TIOIC					1	
→	INSTALLATION DIE CODE =	50		H									\leftarrow	
	DIE COLOR	= Orange				1								
							l		n D		1			
	Beveled wire entry													
В		ւ(ՄL) ^{IIS}	PoHS											В
		UOTED	2002/95/EC											
		LISTED WIRE CONNECTORS ZMVV/2/7/8.E513913												
														
								CF	- FLFST	RA C	ORPO	ORATIO	ON	
							JYA®	76	3. Huand	cun Rd	. Zhong	cun Tow	n.	
						www.h	iuyaco.com	Pa	anyu Dis	st. Gua	ngzhou	511495.		_
Α					WIRE CONNECTORS AND SOLDERING								Α	
				LUGS FOR CODE AND FLEX CABLE										
	00 23-Aug-25	Ruby Feng Sinia Qi	u Celestra S		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRI WROUGHT COPPER DB301243-261 NTS							ROJECTION		
	REV DATE	DWN CHK		ESCRIPTION	ECN	FINISH			36-cp2973	UNIT	INCH	(
		4		3	Δ		2			İ		1		
			•		I					•				